

SPECIFICATIONS

FJ26-280C HYPOID

| Make | | FUSO |
|---|--|------------------|
| Range | | FJ |
| Model | | FJ26-280C HYPOID |
| Model Code | | FJX3WKM2RBSB |
| Axle Layout | | 6x4 |
| Cab | | Extended Day Cab |
| Crew | | 3 seating |
| Vehicle type | | Tipper/Mixer |
| Mass Data (kg) | | |
| GVM | Manufacturer's gross vehicle mass | 27500 |
| GCM | Manufacturer's gross combination mass | 27500 |
| D/T | Permissable max towing drawing vehicle mass | 27500 |
| GA-Front | Manufacturer's front axle mass | 7500 |
| GA-Rear | Manufacturer's rear axle mass | 20000 |
| V | Permissable maximum vehicle mass | 25500 |
| AF | Permissable maximum front axle mass | 7500 |
| AR | Permissable maximum rear axle mass | 18000 |
| UF | Unladen front axle mass | 3890 |
| UR | Unladen rear axle mass | 3910 |
| UT (Tare) | Total unladen mass | 7800 |
| Permissible Body - | | 17700 |
| Fuel Tank (Litres) | Capacity | 200 |
| | | 200 |
| Dimensions (m | m) | |
| OL | Overall length | 7460 |
| OW | Overall width | 2490 |
| CA | Cab to Axle | 3685 |
| OH | Overall height | 2975 |
| FOH | Front overhang | 1460 |
| ROH | Rear overhang | 1050 |
| WB | Wheelbase | 4275 |
| Performance | | |
| Maximum running / Restart Gradeability % | | 61 / 39 |
| Maximum Speed (SA Legislation) | | 80 km/h |
| Minimum turning ra | adius | 8.9 m |
| Standard Equip | oment/features | |
| Air Suspended Driv ELR 3-Point with C Air Conditioner / H 12V Accessory Po Radio AM/FM + US Central Locking an Speedometer, Tac Dual Door Mirrors Variable RPM Com Cruise Control Engine Brake & Ex E-viscous Fan (Inte Differential Lock Bi clutch Wear Indica PSM (parameteriza | wer Outlet SB + AUX nd Electric Windows no, Air and Fuel Gauges + LH Front ans Side Safety Mirrors rol naust Brake rmittent operation fan improves fuel economy) | |
| | nt Cluster with on-board Diagnostic | |
| | | |

| Engine | | |
|-----------------------|--|--|
| Make | FUSO | |
| Model | 6S20 205 | |
| Configuration | Diesel inline 6 | |
| Capacity (cm3) | 6373 | |
| Туре | Four stroke water cooled direct injection diesel engine | |
| Power at RPM | 205 kW @ 2200 rpm | |
| Torque at RPM | 1100 Nm @ 1200 rpm to 1600 rpm | |
| Emission standards | Euro III | |
| Generator | 24V / 80A | |
| Air Cleaner | Dry type - Twin Stage, Paper element | |
| Suction | Snorkel and rain cap | |
| Governor | Electrical control type | |
| Transmission | | |
| Make | FUSO | |
| Model | G131 | |
| Туре | Synchromesh gears | |
| Shift | Manual | |
| No. of gears forward | 9 | |
| First gear ratio | 14.57 | |
| Top gear ratio | 1 | |
| Clutch | | |
| Make | FUSO | |
| Model | 1000 | |
| Туре | Dry-Single plate, Hydraulic actuated control with servo assistance | |
| Diameter (mm) | 395 | |
| | | |
| Drive Axle | | |
| Make | FUSO | |
| Reduction type | Full Floating Type, Tandem, Hypoid Axles | |
| Final Ratio | 5.375 | |
| Suspension | | |
| Front | Parabolic – Multi leaf spring | |
| Rear | Multi leaf spring - Bogie | |
| Stabilisers | Yes | |
| Steering | | |
| | Power assisted – Hydraulic | |
| Brakes | | |
| System type | Pneumatic | |
| Front | Drum | |
| Rear | Drum | |
| ABS + | Yes | |
| Park/Emergency System | Pneumatically operated Spring actuated with hand brake | |
| Auxiliary Brakes | Engine brake & Exhaust brake | |
| Tyres and Rims | | |
| Tyre Sizes | 315/80 R22.5 | |
| Wheel type | Radial, Tubeless | |
| | i iduidi, lubeless | |
| Electrical | | |
| System | 24V | |

Details not binding - subject to change without notice 03/2021



15 000 km maintenance schedule / 400 hrs maintenance schedule

4 Years / 300 000 km Warranty

FJ

DIMENSIONS



