

SPECIFICATIONS

FE8-150 TF AMT

Make		FUSO
Range		Canter
Model		FE8-150 TF AMT
Model Code		FECX1HR3SBJ3
Axle Layout		4x2
Cab		Forward Control
Crew		3 seating
Vehicle type		
GVM	Manufacturer's gross vehicle mass	8550
GCM	Manufacturer's gross combination mass	8500
D/T	Permissible max towing drawing vehicle mass	8500
GA-Front	Manufacturer's front axle mass	3100
GA-Rear	Manufacturer's rear axle mass	6000
V	Permissible maximum vehicle mass	8550
AF	Permissible maximum front axle mass	3100
AR	Permissible maximum rear axle mass	6000
UF	Unladen front axle mass	1655
UR	Unladen rear axle mass	780
UT (Tare)	Total unladen mass	2435
Permissible Body +	Payload	6115
Fuel Tank (Litres)	Capacity	100
Dimensions (mn	n)	
OL	Overall length	7185
OW	Overall width	2145
CA	Cab to Axle	3275
OH	Overall height	2210
FOH	Front overhang	1140
ROH	Rear overhang	1745
WB	Wheelbase	4300
Performance		
Gradeability at Permissible Maximum Weight (V) (tan)		100 km/h
Maximum Speed (SA Legislation)		7.54 m
Standard Equip		
Eco Mode (fuel save Air Conditioner	er)	
Radio (AM/FM/CD) (2 speakers. 10 cm)		
Power Windows (with auto function)		
Central Locking (all doors)		
Electronic Brake force Distribution (EBD) Antilock Braking System (ABS)		
Exhaust Brake System		
Telescopic and tilt steering column with Steering lock		
On-board Diagnostic Supplemental Restraint System (SRS) Driver Air bag		
Lockable fuel tank		
Sun Visor		
Fog lamps		
Standard tool set		
Standard Services		
4 Years / 240 000 km warranty		

Engine	
Make	FUSO
Model	4P10-4AT4
Configuration	Diesel inline 4
Capacity (cm3)	2998
Туре	Four stroke water cooled direct injection diesel engine
Power at RPM	110 kW @ 3500 rpm
Torque at RPM	370 Nm @ 1320 rpm
Emission standards	Euro III
Generator	12 Volt, 110 Amp
Air Cleaner	Dry paper element type
Suction	Snorkel and rain cap
Governor	Electrical control type
Transmission	
	E160
Make	FUSO
Model	M038S5
Type Shift	Synchromesh gears DUONIC AMT
No. of gears forward	6
Top gear ratio	0.701
First gear ratio	5.397
Clutch	
	E160
Make	FUSO
Model	Wat two dual clutch
Type Diameter (mm)	Wet-type dual clutch
Drive Axle	
Make	FUSO
Model Padveties to se	D035H
Reduction type	Single reduction, Hypoid gear 6.166
Suspension	
Front	Laminated leaf springs with shock absorbers
Rear	Laminated leaf springs with shock absorbers and stabilizer
Steering	
	Telescopic and tilt steering column with steering lock
Brakes	
System type	Hydraulic with vacuum servo assistance, dual circuit with ABS+EBD
Front	Disc
Rear	Disc
ABS + EBD	Yes
Park/Emergency System	Internal Expanding type on propeller shaft
Auxiliary Brakes	Exhaust brake
Tyres and Rims	
Tyre Sizes	215/75R17.5
Wheel type	Disc type
Electrical	
System	12V

Details not binding - subject to change without notice 03/2021



25 000 km service intervals on maintenance contract

DIMENSIONS





