

## **SPECIFICATIONS**

## FE7-150 TF AMT

Make		FUSO	
Range		Canter	
Model		FE7-150 TF AMT	
Model Code		FEB71GR3SBJ3	
Axle Layout		4x2	
Cab		Forward Control	
Crew		3 seating	
Vehicle type		Freight Carrier	
Mass Data (kg)			
GVM	Manufacturer's gross vehicle mass	7500	
GCM	Manufacturer's gross combination mass	8500	
D/T	Permissable max towing drawing vehicle mass	8500	
GA-Front	Manufacturer's front axle mass	3100	
GA-Rear	Manufacturer's rear axle mass	6000	
V	Permissable maximum vehicle mass	7500	
AF		3100	
	Permissable maximum front axle mass		
AR	Permissable maximum rear axle mass	6000	
UF	Unladen front axle mass	1560	
UR	Uladen rear axle mass	825	
UT (Tare)	Total unladen mass	2385	
Permissible Body +		5115	
Fuel Tank (Litres)	Capacity	100	
Dimensions (mm)			
OL	Overall length	6685	
OW	Overall width	2035	
CA	Cab to Axle	3275	
ОН	Overall height	2195	
FOH	Front overhang	1140	
ROH	Rear overhang	1695	
WB	Wheelbase	3850	
Performance			
Gradeability at Permissable Maximum Weight (V) (tan ) 31%			
Maximum Speed (SA Legislation)		100 km/h	
Minimum turning radius		6. 82 m	
Standard Equipment/features			
"Eco Mode (fuel saver)			
Air Conditioner			
Radio			
Power Windows (Auto function) Central Locking			
Electronic Brake force Distribution (EBD)			
Antilock Braking System (ABS)			
Exhaust Brake System Telescopic and tilt steering column with Steering lock			
On-board Diagnostic			
Supplemental Restraint System (SRS) Driver Air bag  Lockable fuel tank			
Lockable fuel tank Sun visor			
Fog lamp			
standard tool set"			
Standard Services			
4 Years / 240 000 km warranty			
20 000 km standard service intervals			

Engine		
Make	FUSO	
Model	4P10-4AT4	
Configuration	Diesel inline 4	
Capacity (cm3)	2998	
Туре	Four stroke water cooled direct injection diesel engine	
Power at RPM	110 kW @ 3500 rpm	
Torque at RPM	370 Nm @ 1320 rpm	
Emission standards	Euro III	
Generator	12 Volt, 110 Amp	
Air Cleaner	Dry paper element type	
Suction	Snorkel and rain cap	
Governor	Electrical control type (Common rail system)	
Transmission		
Make	FUSO	
Model	M038S6	
Туре	Synchromesh gears	
Shift	DUONIC AMT	
No. of gears forward	6	
Top gear ratio	0.701	
First gear ratio	5.397	
Clutch		
Make	FUSO	
Model	-	
Туре	Wet-type dual clutch	
Diameter (mm)	-	
Drive Axle		
Make	FUSO	
Model	D035H	
Reduction type	Single reduction, Hypoid gear	
Final Ratio	5.714	
Suspension		
Front	Laminated leaf springs with shock absorbers	
Rear	Laminated leaf springs with shock absorbers and stabilizer	
Steering		
	Telescopic and tilt steering column with steering lock	
Brakes		
	"Hydraulic with vaccum servo assistance, dual circuit with	
System type	ABS+EBD"	
Front	Disc	
Rear	Disc	
ABS +	Yes	
Park/Emergency System	Internal Expanding type on propeller shaft	
Auxiliary Brakes	Exhaust brake	
Tyres and Rims		
Tyre Sizes	215/75R17.5	
Wheel type	Disc type	
Electrical		
System	12V	

Details not binding - subject to change without notice 03/2021



25 000 km service intervals on maintenance contract

## **DIMENSIONS**





