

SPECIFICATIONS

FE4-130 TF AMT

Make		FUSO
Range		Canter
Model		FE4-130 TF AMT
Model Code		FEB21ER3SBJ2
Axle Layout		4x2
Cab		Forward Control
Crew		3 seating
Vehicle type		Freight Carrier
Mass Data (kg)		
GVM	Manufacturer's gross vehicle mass	4900
GCM	Manufacturer's gross combination mass	6000
D/T	Permissable max towing drawing vehicle mass	6000
GA-Front	Manufacturer's front axle mass	1950
GA-Rear	Manufacturer's rear axle mass	3700
V	Permissable maximum vehicle mass	4900
AF	Permissable maximum front axle mass	1950
AR	Permissable maximum rear axle mass	
UF	Unladen front axle mass	3700
UR	Uladen rear axle mass	555
UT (Tare)	Total unladen mass	2025
Permissible Body +	<u> </u>	2875
Fuel Tank (Litres)	Capacity	100
Dimensions (mn	n)	
OL	Overall length	5935
OW	Overall width	1995
CA	Cab to Axle	2825
ОН	Overall height	2165
FOH	Front overhang	1140
ROH	Rear overhang	1395
WB	Wheelbase	3400
Performance		
Gradeability at Perm	nissable Maximum Weight (V) (tan)	54%
Maximum Speed (SA Legislation)		100 km/h
Minimum turning radius		5.5 m
Standard Equip		
Eco Mode (fuel save Electronic Brake for	er) ce Distribution (EBD)	
Antilock Braking System (ABS)		
Exhaust Brake System		
Telescopic and tilt steering column with Steering lock		
On-board Diagnost		
Reverse warning Bu	aint System (SRS) Driver Air bag uzzer	
Standard tool set		
Seat belt (3 points type with ELR x 2.2 points type x 1)		
Sun visor		
All lamps with E.e. marks		
Side door Beam		
4 Years / 240 000 k	rm warranty	
20 000 km standard service intervals		
95 000 km con igo intervale en maintenance contract		

Engine			
Make	FUSO		
Model	4P10-4AT2		
Configuration	Diesel inline 4		
Capacity (cm3)	2998		
Туре	Four stroke water cooled direct injection diesel engine		
Power at RPM	96 kW @ 3500 rpm		
Torque at RPM	300 Nm @ 1300 rpm		
Emission standards	Euro III		
Generator	12 Volt, 110 Amp		
Air Cleaner	Dry paper element type		
Suction	Snorkel and rain cap		
Governor	Electrical control type (Common rail system)		
Transmission			
Make	FUSO		
Model	M038S6		
Туре	Synchromesh gears		
Shift	DUONIC AMT		
No. of gears forward	6		
Top gear ratio	0.701		
First gear ratio	5.397		
Clutch			
	FUIDO		
Make	FUSO		
Model	Mot to so shoot all table		
Type	Wet-type dual clutch		
Diameter (mm)	-		
Drive Axle			
Make	FUSO		
Model	D3H		
Reduction type	Single reduction, Hypoid gear		
Final Ratio	4.875		
Suspension			
Front	Double wisbone independent suspension		
Rear	with coil spring & shock absorber Laminated leaf springs with shock absorbers and stabilizer		
Steering			
Otooning	Telescopic and tilt steering column with steering lock		
2.1	relescopic and till steering column with steering lock		
Brakes			
System type	Hydraulic with vacuum servo assistance, dual circuit with ABS+EBD		
Front	Disc		
Rear	Disc		
ABS +	Yes		
Park/Emergency System	Internal Expanding type on propeller shaft		
Auxiliary Brakes	Exhaust brake		
Tyres and Rims			
Tyre Sizes 195/75R16			
Wheel type	Disc type		
	Disc type		
Electrical			
System	12V		

Details not binding - subject to change without notice 03/2021



25 000 km service intervals on maintenance contract

DIMENSIONS





