

SPECIFICATIONS

FE7-136 TD MT

Make		FUSO	
Range		Canter	
Model		FE7-136 TD MT	
Model Code		FE85PG6SRBJ1	
Axle Layout		4x2	
Cab		Forward Control	
Crew		3 seating	
Vehicle type		Freight Carrier	
Mass Data (kg)			
GVM	Manufacturer's gross vehicle mass	7500	
GCM	Manufacturer's gross combination mass	8500	
D/T	Permissible max towing drawing vehicle mass	8500	
GA-Front	Manufacturer's front axle mass	2850	
GA-Rear	Manufacturer's rear axle mass	5400	
V	Permissible maximum vehicle mass	7500	
AF	Permissible maximum front axle mass	2850	
AR	Permissible maximum rear axle mass	5400	
UF	Unladen front axle mass	1655	
UR	Unladen rear axle mass	805	
UT (Tare)	Total unladen mass	2460	
Permissible Body +		5040	
Fuel Tank (Litres)	Capacity	100	
Dimensions (mn	n)		
OL	Overall length	6735	
OW	Overall width	1995	
CA	Cab to Axle	3285	
ОН	Overall height	2260	
FOH	Front overhang	1145	
ROH	Rear overhang	1700	
WB	Wheelbase	3850	
Performance			
Gradeability at Permissible Maximum Weight (V) (tan)		38%	
Maximum Speed (SA Legislation)		100 km/h	
Minimum turning radius		6.8m	
Standard Equip	ment/features		
Antilock Braking Sys			
Exhaust Brake Syste			
Lockable Fuel Tank Cap			
Outside mirror with long stay			
Seatbelt for driver, front centre and driver assistant			
Ashtray on door for driver and assistant Cigarette lighter			
Sunvisor for Driver and assistant			
Interior mirror			
Heater and defroster			
Dual type electric horn			
All lamps with E.e mark Telescopic and tilt steering column with Steering lock			
Tachometer			
Standard tool set			
Standard Services			

Engine		
Make	FUSO	
Model	4D34-2AT4	
Configuration	4 inline	
Capacity (cm3)	3908	
Туре	Four stroke water cooled direct injection diesel engine	
Power at RPM	100@2 900	
Torque at RPM	370@1 600	
Emission standards	Euro II	
Generator	24 Volt, 50 Amp	
Air Cleaner	Dry paper dual elemenr type	
Suction	Snorkel and rain cap	
Governor	All speed mechanical governor	
Transmission		
Make	FUSO	
Model	M035S5	
Туре	5 forward and 1 reverse, synchromesh gears	
Shift	Manual	
No. of gears forward	5	
First gear ratio	5.380	
Top gear ratio	0.722	
Clutch		
Make	FUSO	
Model	C4W30D	
Туре	Hydraulic control, Single Dry Plate	
Diameter (mm)	Trydradiic control, Single Dry Flate	
	550	
Drive Axle		
Make	FUSO	
Model	D035H	
Reduction type	Single reduction, Hypoid gear	
Final Ratio	5.714	
Suspension		
Front	Laminated leaf springs with shock absorbers	
Rear	Laminated leaf springs with shock absorbers	
Steering		
	Telescopic and tilt steering column with steering lock	
Brakes		
System type	Hydraulic with vacuum servo assistance, dual circuit with ABS	
Front	Drum	
Rear	Drum	
ABS	Yes	
Park/Emergency System	Internal Expanding type on propeller shaft	
Auxiliary Brakes	Exhaust brake	
Tyres and Rims		
Tyre Sizes 215/75R17.5		
Wheel type	Drum Type	
Electrical		
System	24V	

Details not binding - subject to change without notice 03/2021



4 Years / 240 000 km warranty
15 000km maintenance schedule

DIMENSIONS





