

SPECIFICATIONS

FE4-130 TF MT

Make		FUSO
Range		Canter
Model		FE4-130 TF MT
Model Code		FEB21ER4SBJ2
Axle Layout		4x2
Cab		Forward Control
Crew		3 seating
Vehicle type		Freight Carrier
Mass Data (kg	a)	
GVM	Manufacturer's gross vehicle mass	4900
GCM	Manufacturer's gross combination mass	6000
D/T	Permissable max towing drawing vehicle mass	6000
GA-Front	Manufacturer's front axle mass	1950
GA-Rear	Manufacturer's rear axle mass	3700
V	Permissable maximum vehicle mass	4900
AF	Permissable maximum front axle mass	1950
AR	Permissable maximum rear axle mass	3700
UF	Unladen front axle mass	1440
UR	Uladen rear axle mass	565
UT (Tare)	Total unladen mass	2005
Permissible Body		2895
Fuel Tank (Litres)	Capacity	100
Dimensions (r		
OL	Overall length	5935
ow	Overall width	1995
CA	Cab to Axle	2825
ОН	Overall height	2165
FOH		1140
	Front overhang	
ROH	Rear overhang Wheelbase	1395
WB	Wheelbase	3400
Performance		
Gradeability at Permissable Maximum Weight (V)		55%
Maximum Speed	(Legislation) (Legislation)	100 km/h
Minimum turning radius		5.5 m
Standard Equ	ipment/features	
Eco Mode (fuel sa	aver)	
Electronic Brake force Distribution (EBD)		
Antilock Braking System (ABS) Exhaust Brake System		
Telescopic and tilt steering column with Steering lock		
On-board Diagnostic		
-	straint System (SRS) Driver Air bag	
Reverse warning	Buzzer	
Standard tool set		
seat belt (3 points Sunvisor	s type with ELR x 2.2 points type x 1)	
	e. marks Side door Beam	
Independent front suspension ensures a comfortable ride		

Engine		
Make	FUSO	
Model	4P10-4AT2	
Configuration	Diesel inline 4	
Capacity (cm3)	2998	
Туре	Four stroke water cooled direct injection diesel engine	
Power at RPM	96 kW @ 3500 rpm	
Torque at RPM	300 Nm @ 1300 rpm	
Emission standards	Euro III	
Generator	12 Volt, 110 Amp	
Air Cleaner	Dry paper element type	
Suction	Snorkel and rain cap	
Governor	Electrical control type (Common rail system)	
Transmission		
Make	FUSO	
Model	M038S5	
Туре	Synchromesh gears	
Shift	Manual	
No. of gears forward	5	
Top gear ratio	0.723	
First gear ratio	5.494	
Clutch		
Make	FUSO	
Model	C3W28	
Туре	Hydraulic Single Dry Plate	
Diameter (mm)	275	
Drive Axle		
Make	FUSO	
Model	D3H	
Reduction type	Single reduction, Hypoid gear	
Final Ratio	4.875	
Suspension		
Front	Double wisbone independent suspension	
Rear	with coil spring & shock absorber Laminated leaf springs with shock absorbers and stabilizer	
Steering		
	Telescopic and tilt steering column with steering lock	
Brakes	isosoopis and an stooming column. Man stooming look	
	Hydraulic with vacuum servo assistance,	
System type	dual circuit with ABS+EBD	
Front	Disc	
Rear	Disc	
ABS + EBD	Yes	
Park/Emergency System	Internal Expanding type on propeller shaft	
Auxiliary Brakes	Exhaust brake	
Tyres and Rims		
Tyre Sizes	195/75R16C	
Wheel type	Disc type	
Electrical		
System	12V	

Details not binding - subject to change without notice 03/2021



25 000 km service intervals on maintenance contract

Standard Services
4 Years / 240 000 km warranty
20 000 km standard service intervals

www.fuso.co.za

DIMENSIONS





